

PANTHER MFW311-K

The industry renowned PANTHER range of Diesel-Driven Welder-Generators is now available in a 200Amp Single-Phase, two 300Amp Multi-Phase and a 500Amp Multi-Phase Dual Operator model. These are the MFW200-K, MFW307-K, **MFW311-K** and MFW500SS-K, all of which utilise a Kubota Engine as their power source and engine management system.

We also have access to a full range of spare parts for previous models, including the Panther 270, 304, 306, 307, 310 and 310M. Many parts for these machines are currently kept in stock in the UK.



- Reliable performance
- Petrochemical Approved Standard
- Safety features - RCB's fitted as standard
- Simultaneous use of welder and AC power
- Auto-idling system
- Low noise levels
- Easy maintenance
- Large fuel tank
- Electronic engine governor
- Manufacturers EMS
- EC Approved

NORTH (HEAD OFFICE):
LORENY INDUSTRIAL ESTATE AYR ROAD KILMARNOCK AYRSHIRE KA1 5LE
TEL: 01563 529435 FAX: 01563 523510

MIDLANDS:
108 HIGHFIELDS ROAD BILSTON WOLVERHAMPTON WEST MIDLANDS WV14 0LD
TEL: 01902 495686 FAX: 01902 496461

SOUTH:
UNIT 1 OMNI BUSINESS CENTRE OMEGA PARK ALTON HAMPSHIRE GU34 2QD
TEL: 01420 546855 FAX: 01420 546856

sales@panthereurope.com www.panthereurope.com

SPECIFICATIONS

MFW311-K

GENERATOR

DC WELDER

Rated Output	kW	8.32
Rated Current	A	300
Rated Voltage	V	30.8
Current Range	-	30~300
Open-circuit Voltage	V	85
Rated duty-cycle	%	60
Rated Speed	min ⁻¹	3,000
Type		Rectified DC. Output type
Applicable Electrode	mm	2.0~6.0

Aux. Power

Rated Output	kVA	10	3.68
Rated Voltage	V	400	230
Rated Current	A	14.5	16
No. of Phase	-	3-phase/4wires	1-phase/2wires
Power Factor	%	80	100
Rated Output	kW	3.52	
Rated Voltage	V	110 (Center Tap Earth Type)	
Rated Current	A	32	
No. of Phase	-	1-phase/2wires	
Power Factor	%	100	
Frequency	Hz	50	
Rated Speed	min ⁻¹	3,000	
Rating	-	Continuous	
Excitation	-	Brushless	

SET ENGINE

Model & Maker	-	D905 (KUBOTA)
Type	-	4-cycle, water-cooled diesel engine
Cylinder arrangement	-	3-L
Total displacement	cc	898
Rated output	kW	14.2
Rated speed	min ⁻¹	3,000
Cooling system	-	Water-cooled by radiator type
Driving system	-	Direct coupling with the engine
Fuel oil	-	Diesel light oil
Starting system	-	Electric motor, 12V
Fuel tank capacity	L	37
Battery capacity	-	55B24L (12V-36AH/5HR)
Dimensions LxWxH (approx.)	mm	1,300 x 710 x 805
Net dry mass (approx.)	kg	410
Operating mass (approx.)	kg	449



Optional Extras

- 2-Wheel Road Tow Assembly
- Remote Control Unit c/w Cable
- Chalwyn Valve
- Spark Arrestor
- 2kg Fire Extinguisher c/w Bracket
- Full Petro-Chemical Specification
- Galvanised Dip Trays
- Wheel-Barrow Type Fuel Bowsers

